

ECE 461 – Internetworking

Problem Sheet 2

Instructions (read carefully):

- Try to solve the problems on your own.
- Solutions will be discussed in tutorials.

Problem 1. Describe how class A, B, and C IP addresses are recognized in a binary representation of IP addresses ?

Problem 2.

- a) Why is a subnet of all zeros or all ones cannot be used in a classful routing environment?
- b) How many subnets are available if a class C address has six bits of subnetting? How many host addresses are available per subnet. (Hint: The problem statement of (a) contains a part of your answer.)

Problem 3. How would you express the entire Class B address space as a single CIDR advertisement?

Problem 4. Assume that you have been assigned the 198.42.180.0/22 block of IP addresses.

- a) Specify an extended network prefix that allows the creation of 200 hosts on each subnet.
- b) With your answer to (a), what is the maximum number of hosts that can be assigned to each subnet?
- c) With your answer to (a), what is the maximum number of subnets that can be defined?
- d) Give the IP address (in CIDR notation) of one of these subnets. Give the broadcast address for this subnet.

Problem 5. Aggregate the following set of four /24 IP network addresses to the highest degree possible.

212.56.132.0/24
212.56.133.0/24
212.56.134.0/24
212.56.135.0/24

Problem 6. Aggregate the following set of four /24 IP network addresses to the highest degree possible.

212.56.146.0/24
212.56.147.0/24
212.56.148.0/24
212.56.149.0/24